



**Current Transformers**



Window Diameter: 1.0"  
Continuous Thermal Rating: 1.33 at 30 C. amb.;  
1.0 at 55 C. amb. Average.

Application: Ammeters and Wattmeters and Relays.  
Insulation Class: 0.6 kV. BIL 10kV. full wave 50-400 Hz.  
Fully encapsulated.


Standard 5 amp secondary, others available.



**10252ARW**



**10252ASB**



**10252ASH**

**Model nbr.**

**10252ARW**  
**ASB**  
**ASH**

To order, please complete the model number with the appropriate suffix.  
eg. 10252ASH-100

- ▶ Flexible leads are UL 3173 125 degree C.
- ▶ CSA approved, # 16 AWG 24" long. Non standard length to be specified.
- ▶ Terminals are brass No. 10-32 UNC.
- ▶ Approximate weight 0.5 lb.
- ▶ Additional ratios available.

Catalogue nbr. Suffix	Current Ratio	VA for ±1% Class	ANSI Metering Class @ 60Hz			
			BO.1	BO.2	BO.5	BO.9
-50	50:5	±2% 2.5	2.4	-	-	-
-60	60:5	2.5	2.4	2.4	-	-
-75	75:5	3.5	2.4	2.4	-	-
-80	80:5	4.0	1.2	2.4	-	-
-100	100:5	5.0	0.6	0.6	-	-
-120	120:5	5.0	0.6	0.6	-	-
-125	125:5	5.0	0.6	0.6	-	-
-150	150:5	10.0	0.6	0.6	2.4	-
-200	200:5	12.5	0.3	0.6	1.2	-
-250	250:5	15.0	0.3	0.6	1.2	-
-300	300:5	20.0	0.3	0.3	0.6	1.2