




Current Transformers


Window Diameter: 1.50"
Continuous Thermal Rating: 1.33 at 30 C. amb.;
1.0 at 55 C. amb. Average.

Application: Ammeters and Wattmeters & Watthourmeters.
Insulation Class: 0.6 kV. BIL 10kV. full wave 50-400 Hz.
Fully encapsulated.

Standard 5 amp secondary, others available.



15352RW



15352RWB

To order, please complete the model number with the appropriate suffix.
eg. 15352RW-100

- ▶ Flexible leads are UL 3173 125 degree C.
- ▶ CSA approved, # 16 AWG 24" long. Nonstandard length to be specified.
- ▶ Approximate weight 0.5 lb.
- ▶ Additional ratios available.

Model nbr.	Catalogue nbr. Suffix	Current Ratio	Accuracy @ 60Hz	Burden VA @ 60Hz
15352RW	-50	50:5	± 2%	1.0
15352RWB	-75	75:5	± 2%	1.5
	-100	100:5	± 2%	2.0
	-150	150:5	± 1%	5.0
	-200	200:5	± 1%	5.0
	-250	250:5	± 1%	10.0
	-300	300:5	± 1%	12.5
	-400	400:5	± 1%	12.5
	-500	500:5	± 1%	20.0
	-600	600:5	± 1%	25.0
	-750	750:5	± 1%	25.0
	-800	800:5	± 1%	25.0
	-1000	1000:5	± 1%	25.0
	-1200	1200:5	± 1%	30.0