



Current Transformers


Window Diameter: 2.00"
Continuous Thermal Rating: 1.33 at 30 C. amb.;
1.0 at 55 C. amb. Average.

Application: Ammeters and Wattmeters & Relays.
Insulation Class: 0.6 kV. BIL 10kV. full wave 50-400 Hz.
Fully encapsulated.

Standard 5 amp secondary, others available.



2035RW



2035RWB

To order, please complete the model number with the appropriate suffix.
eg. 2035RW-100

- ▶ Flexible leads are UL 3173 125 degree C.
- ▶ CSA approved, # 16 AWG 24" long. Nonstandard length to be specified.
- ▶ Approximate weight 0.7 lb.
- ▶ Additional ratios available.

Model nbr.	Catalogue nbr. Suffix	Current Ratio	Accuracy @ 60Hz	Burden VA @ 60Hz
2035RW	-50	50:5	± 3%	0.5
2035RWB	-75	75:5	± 2%	0.5
	-100	100:5	± 2%	1.0
	-150	150:5	± 1%	2.5
	-200	200:5	± 1%	4.0
	-250	250:5	± 1%	6.0
	-300	300:5	± 1%	7.5
	-400	400:5	± 1%	10.0
	-500	500:5	± 1%	12.5
	-600	600:5	± 1%	12.5
	-750	750:5	± 1%	12.5
	-800	800:5	± 1%	12.5
	-1000	1000:5	± 1%	12.5
	-1200	1200:5	± 1%	12.5