





Current Transformers

Window Diameter: 2.0"
Continuous Thermal Rating: 1.33 at 30 C. amb.;
1.0 at 55 C. amb. Average.

Application: Ammeters and Wattmeters and Relays.
Insulation Class: 0.6 kV. BIL 10kV. full wave 50-400 Hz.
Fully encapsulated.

Standard 5 amp secondary, others available.



2040ARW

2040ARWB

Model nbr.

2040ARW
ARWB

To order, please complete the model number with the appropriate suffix.
eg. 2040ARWB-100

- ▶ Flexible leads are UL 3173 125 degree C.
- ▶ CSA approved, # 16 AWG 24" long. Nonstandard length to be specified.
- ▶ Approximate weight 1.25 lb.
- ▶ Additional ratios available.

Catalogue nbr. Suffix	Current Ratio	VA for ±1% Class	ANSI Metering Class @ 60Hz			
			BO.1	BO.2	BO.5	BO.9
-100	100:5	1.0	2.4	-	-	-
-150	150:5	5.0	1.2	1.2	-	-
-200	200:5	5.0	0.6	1.2	-	-
-250	250:5	7.5	0.6	0.6	1.2	-
-300	300:5	12.0	0.3	0.3	1.2	-
-400	400:5	15.0	0.3	0.3	0.6	-
-500	500:5	25.0	0.3	0.3	0.6	-
-600	600:5	30.0	0.3	0.3	0.3	-
-750	750:5	30.0	0.3	0.3	0.3	-
-800	800:5	35.0	0.3	0.3	0.3	-
-1000	1000:5	35.0	0.3	0.3	0.3	0.6
-1200	1200:5	40.0	0.3	0.3	0.3	0.6