

877-798-7287

Catalogue nbr. Suffix	Current Ratio	ANSI Metering Class @ 60Hz				
		BO.1	BO.2	BO.5	BO.9	B1.1
-10	10:5	0.3	0.3	0.3	0.6	1.2
-20	20:5	0.3	0.3	0.3	0.6	1.2
-25	25:5	0.3	0.3	0.3	0.6	1.2
-30	30:5	0.3	0.3	0.3	0.6	1.2
-40	40:5	0.3	0.3	0.3	0.6	1.2
-50	50:5	0.3	0.3	0.3	0.6	1.2
-75	75:5	0.3	0.3	0.3	0.6	1.2
-100	100:5	0.3	0.3	0.3	0.6	1.2
-150	150:5	0.3	0.3	0.3	0.6	1.2
-200	200:5	0.3	0.3	0.3	0.6	1.2
-250	250:5	0.3	0.3	0.3	0.6	1.2
-300	300:5	0.3	0.3	0.3	0.6	1.2
-400	400:5	0.3	0.3	0.3	0.6	1.2
-500	500:5	0.3	0.3	0.3	0.6	1.2
-600	600:5	0.3	0.3	0.3	0.6	1.2

CURRENT TRAWSFORMERS

LOW VOLTAGE

- ▶ Standard secondary voltage is 120; other ratios available
- ▶ VA ratings from 75 to 750
- ▶ Completely encapsulated
- ▶ Metering grade accuracy
- ▶ UL and Canadian UL recognized components
- ▶ RoHS



Ratio	Primary Voltage
0.58:1	69.4
1:1	120
1.73:1	208
2:1	240
2.4:1	288
3:1	360
4:1	480
5:1	600

MEDIUM VOLTAGE to 15kV



- ▶ All ratios are designed for 60 Hz operation except where noted.
- ▶ Thermal burden ratings are for 120V secondaries.
- ▶ Larger KVA ratings on request.
- ▶ Approximate weight 55 lb.
- ▶ Fully encapsulated under vacuum using a 35 Kv epoxy resin.
- ▶ Tested for partial discharge to IEC Standards.

Model nbr. CPT5K-60-1

Catalogue nbr. Suffix	Ratio	Primary Voltage	Thermal Rating
-2400	20:1	2400	1.0KVA
⊗ -3300	30:1	3300	0.8KVA
-4160	34.7:1	4160	1.0KVA
-4800	40:1	4800	1.0KVA
⊗ -6600	60.7:1	6600	0.6KVA
-7200	60:1	7200	0.6KVA

⊗ Specifically designed for 50Hz operation and 110vac secondary volts.

We also have a complete selection of meters & relays.



Distributed by:

