


**Multi Ratio**  
**Current Transformers**

Window Diameter: 7.31"  
Plastic case.  
Brass screws 10-32 UNC

Application: Ammeters and Wattmeters and Relays.  
Insulation Class: 0.6 kV. BIL 10kV. full wave 50-400 Hz.  
Standard 5 amp secondary, others available.



**CUSTOM OPTIONS:**

- Different Ratios
- IEC Ratios/Accuracies
- Non-standard thermal rating
- Different secondary termination
- Special mounting needs

CATALOG NUMBER	CURRENT RATIO	RELAY CLASS	ANSI METERING CLASS @ 60 HZ					THERMAL RATING	
			B0.1	B0.2	B0.5	B0.9	B1.8	@ 30° C	@ 55° C
CT355-500-01	50:5	C10	4.8	4.8	-	-	-	2.0	2.0
CT355-500	50:5	C20	4.8	4.8	-	-	-	2.0	2.0
CT355-750	75:5	C20	2.4	2.4	-	-	-	2.0	2.0
CT355-101	100:5	C20	1.2	2.4	4.8	4.8	-	2.0	2.0
CT355-151	150:5	C50	0.6	0.6	1.2	2.4	4.8	2.0	2.0
CT355-201	200:5	C50	0.3	0.3	0.6	1.2	2.4	2.0	2.0
CT355-251	250:5	C50	0.3	0.3	0.6	1.2	2.4	2.0	2.0
CT355-301	300:5	C100	0.3	0.3	0.3	0.6	1.2	2.0	2.0
CT355-401	400:5	C100	0.3	0.3	0.3	0.3	0.6	2.0	2.0
CT355-501	500:5	C100	0.3	0.3	0.3	0.3	0.6	2.0	2.0
CT355-601	600:5	C200	0.3	0.3	0.3	0.3	0.3	2.0	2.0
CT355-751	750:5	C200	0.3	0.3	0.3	0.3	0.3	2.0	2.0
CT355-801	800:5	C200	0.3	0.3	0.3	0.3	0.3	2.0	2.0
CT355-102	1000:5	C200	0.3	0.3	0.3	0.3	0.3	1.5	1.33
CT355-122	1200:5	C400	0.3	0.3	0.3	0.3	0.3	1.5	1.0
CT355-152	1500:5	C400	0.3	0.3	0.3	0.3	0.3	1.5	1.0
CT355-162	1600:5	C400	0.3	0.3	0.3	0.3	0.3	1.33	1.0
CT355-202	2000:5	C400	0.3	0.3	0.3	0.3	0.3	1.33	1.0
CT355-252	2500:5	C400	0.3	0.3	0.3	0.3	0.3	1.0	0.8
CT355-302	3000:5	C800	0.3	0.3	0.3	0.3	0.3	1.0	0.8
CT355-322	3200:5	C800	0.3	0.3	0.3	0.3	0.3	1.0	0.8
CT355-352	3500:5	C800	0.3	0.3	0.3	0.3	0.3	1.0	0.8
CT355-402	4000:5	C800	0.3	0.3	0.3	0.3	0.3	1.0	0.6
CT355-502	5000:5	C800	0.3	0.3	0.3	0.3	0.3	1.0	0.6
CT355-602	6000:5	C800	0.3	0.3	0.3	0.3	0.3	0.8	0.6

**DIMENSIONS: ALL ARE IN INCHES [mm]**

